

AQUAPAD



5L

1L

PRODUCT DISRIPTION

Ciranova Aquapad is a waterborne wood stain to colour all kind of wood for interior use. Aquapad gives the wood a uniform appearance and does the nerve come into its own. Due to its special composition and ease of use Aquapad is ideal for coloring large surfaces such as parquet.

TECHNICAL DATA

COLOR	AVAILABLE IN 16 COLORS
SOLID CONTENT	DEPENDING OF THE COLOR
DENSITY	DEPENDING OF THE COLOR
VISCOSITY	+/- 11" DIN 4 AT 20°C

PREPARATION

Sand the wood before with 120 to 150 grit sandpaper. After sanding the sanding dust must be carefully removed.

USER INSTRUCTIONS

Stir well before use. It is recommended to test the chosen color first before you treat the entire surface. During use, the Aquapad must be stired frequently.

To finish with a varnish (Aquafix range) a hardener can be added (in Summer: 5% hardener - in winter: 10% hardener) or the Aquapad must first be blocked with a Hardwaxoil Magic or Full Solid (Clear, Natural White or Natural).

Take in account that there is a potlife of +/- 3 hours when the hardener is added. It's recommended only to sand after applying the first protection layer. When sanding after application of the Aquapad, there is a risk of color difference.

Aquapad can be applied directley with a buffing machine. If the Aquapad is applied with a roller or brush you must egalize with a buffing machine (white or gray pad). Don't leave used pads on the floor to avoid color differences.



DRYING TIMES

Dry after +/- 3 to 4 hours



APPLYING QUANTITY

10 to 15 m² / liter depending on the type of wood.

AFTER TREATMENT

After drying, the Aquapad must be protected by one of our Hardwaxoils, waxes or varnishes (only when a hardener was used).

PRODUCT INFORMATION

All colors can be mixed and diluted with water. Shelf life: 1 year in closed original packaging.

SPECIAL QUALITIES

Aquapad is not frost resistant, do not use or transport below 5 °C. Do not use materials that can rust. The final color depends on the wood, sanding, and the quantity applied. Therefore it is recommended to always test the color on the wood!

Ciranova[®] products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

PRODUCED BY DEBAL COATINGS NV

Industrieweg 29 – B 8800 Beveren-Roeselare
tel +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48
www.ciranova.be ciranova@ciranova.be