

# OCULTO



1L

5L

Ciranova® products are made for the professional user. The instructions specified in the data sheet are formulated after necessary tests were performed and after years of experience. However, they are drawn to our best knowledge and ability. The user must test the application of the product in the for him applicable conditions. Guarantee can not be derived out the text of this technical description.

## PRODUCED BY DEBAL COATINGS NV

Industrieweg 29 – B 8800 Beveren-Roeselare  
tel +32 (0) 51 30 11 40 fax +32 (0) 51 31 26 48  
www.ciranova.be ciranova@ciranova.be

## PRODUCT DESCRIPTION

Water based impregnation oil for parquet and wooden furniture. Only for interior use. Particular suitable for interiors where a natural finish is needed such as parquet, veneer and other wooden objects.

OCULTO is also an Anti-slip finish and with the addition of UV inhibitors, it prevents the wood from yellowing.

## TECHNICAL DATA

VISCOSITY	+/- 16 SEC (DIN 4MM)
SOLID CONTENT	+/- 28% BY WEIGHT
DENSITY	+/- 1 KG/L
GLOSS	< 5
DILUTION	CLEAR

CONFORM THE EUROPEAN DECO-PAINT DIRECTIVE 2010

## PREPARATION

Surface: Solid wood, engineered wood. Sand the surface with grain 100-150 and afterwards remove sanding dust.

## USER TIPS

Use Oculito as a sealer and topcoat and to apply in 3 layers. Mix or stir the product well before use and don't dilute it. Application is done by a brush or roller. Apply the layers wet in wet to avoid overlapping. When the first layer is dry, apply the second layer as the first layer. When the second layer is dry, sand with grain 150-180, remove sand dust and apply the third layer. An optional hardener may be added for improved durability.



## DRYING TIMES

Dust free: 20 to 30 minutes

Sandable: 2 to 4 hours

Chargeable after 24 hours

The drying time is strongly depending on the applied quantity, the temperature, air humidity and the ventilation of the room. Through a higher temperature and good ventilation, drying time is limited.



## APPLYING QUANTITY

10-12 m<sup>2</sup>/liter per coat

## AFTER TREATMENT

Use Hard Floor fresh Ciranova for regular maintenance.

## PRODUCT INFORMATION

12 months in well-closed and original packing.

not frost-durable.

Pot life with hardener: +/- 3 hours.

## SPECIAL QUALITIES

Use only stainless material. After use, rinse the material directly with water. This product cannot be poured into sewerage. If a stain on the wood is needed, only use Ciranova AQUAPAD + HARDENER.

Be aware of discoloration or detachment because of wood compounds like resins or tannin.