

Hard Floor Matt Polish



750ml

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-
Roeselare Belgium tel. +32 (0) 51 30 11 40
fax +32 (0) 51 31 26 48
ciranova@ciranova.be

PRODUCT DESCRIPTION

A waterborne environmental friendly protective refresher for varnished or lacquered wooden floors and parquet floors.

TECHNICAL DATA

VISCOSITY	Like water
APEARANCE	Milky
SOLID CONTENT	+/- 22% by weight
pH-VALUE	8,6 at 20°C
DILUTION	water
DENSITY	+/- 1,02 kg/l at 20°C
GLOSS	Matt
NMP FREE	

CONFORM THE EUROPEAN DECO-PAINT DIRECTIVE 2010

USE

For all types of indoors unwaxed, varnished, sealed or lacquered wooden floors and parquet floors. Coverage: 30 - 40 m²/l.

-New varnished or lacquered floor: wait 14 days after application of the finish before applying Hard floor polish. Remove all loose dirt with a vacuum, brush or sweeper.

-Unpolish varnished or lacquered floor: Use first Hard floor cleaner on very dirty floors to remove all greasy and dried up dirt stains.

APPLICATION

Pour some Hard floor Matt polish on the floor. Spread it out with a clean, non-fluffing cloth or mop and finish it in strokes in the direction of the grain of the wood floor. Continue in sections until the entire floor is done. Keep your cloth wet and do not use it to spars otherwise streaks may occur. Finish in even strokes otherwise a cloudy finish will occur. Clean floor completely, otherwise uneven sheen will occur.

SPECIAL QUALITIES

Keep out of the reach of children. Do not mix with other cleaning products. If swallowed, seek medical advice immediately and show this container or label.

-Hard floor polish is not a cleaning product, it does not remove dirt or stains from the floor. As cleaning product use Hard Floor Cleaner.

-Do not use the product on waxed or oiled floors.

-Test the product first on a small surface, on very absorbing water sensible woods like berk and guatambo it may decolor the wood slightly.

-Do not mix with other cleaning products.

AFTER TREATMENT

For regular maintenance, use Hard floor fresh. When the general aspect of the floor starts to dull, apply a new coat of Hard floor polish. On floors with normal traffic, this is about 4 times a year. After 5 to 10 coats it is better to remove the coats Hard floor polish with Hard floor cleaner and start over.