

# Flooring wax



5L 1L

As with all wood finishing always do a test area first to safeguard against an undesirable outcome. This technical data sheet is merely a guide and not a guarantee. All products are formulated to the best of our knowledge. The information is given as a result of many years experience. This product has had extensive tests carried out.

## Produced by Debal Coatings nv

Industrieweg 29 - 8800 Beveren-Roeselare  
Belgium  
tel. +32 (0) 51 30 11 40  
fax +32 (0) 51 31 26 48  
ciranova@ciranova.be

## PRODUCT DESCRIPTION

A traditional water repellent flooring wax made from natural and synthetic waxes. A silicone resin improves the water repellency.

## TECHNICAL DATA

APPEARANCE	<b>cream</b>
ODOUR	<b>solvent smell</b>
DENSITY	<b>0,75</b>
SOLID CONTENT	<b>20%</b>

## USE

To polish waxed or varnished furniture, beams, doors and wooden floors.

## PREPARATION

Sand the wood well. For oak use a 150 grit sandpaper. For pine use 220 grit sandpaper. You can use the wax directly on the wood. It is also possible to use Aquacolor, reactive stain or Aquavintage first to color the wood. To improve the water protection, you can also first apply a parquet oil (Basic oil Ciranova) or a varnish. Afterwards you can apply the Parquet Wax.

## USER TIPS

Apply a thin coat with a sponge, paintbrush or cloth. When dry buff with a soft cloth or buffing machine (white pad).



## DRYING TIMES

Sponge coat: 30 minutes. Drying time is strongly depending on the amount of fluid used, temperature, humidity en ventilation.



## APPLYING QUANTITY

7-12 m<sup>2</sup>/l. Depending on how well the wood is sanded and the type of wood.

## AFTER TREATMENT

Once dry, polish vigorously with a soft cloth until the wood gets a beautiful shine. Do not apply varnish over wax polish. Store below 20°C.

## PRODUCT INFORMATION

Ciranova<sup>®</sup> Flooring Wax is flammable and should be stored in a safe place. Available colours: clear, yellow and brown. Storage: store in a well ventilated place for up to 2 years. Store below 20°C.

## SPECIAL QUALITIES

A creamy product that is very easy to apply, with a high shine and a fast drying time. Ciranova<sup>®</sup> Flooring Wax is made from a mixture of natural and synthetic raw materials. It contains no toluene and is user-friendly. It is especially developed to sponge. It gives a high and durable shine. This wax gives a good water repellency.