



Linfo-Opax OPR

**MATTE FINISH FOR OILED PARQUET
FOR INTERIORS**

COMPOSITION

Wax-resin emulsions, microcrystalline wax, paraffin wax, carnauba wax, beeswax, polyethylene wax, propolis, essences, alcohol, water.

PROFILE

LINFO-OPAX is an emulsion of fine waxes and propolis that increases the protection of wooden floors treated with vegetable oils or paste waxes, giving a natural finish.

IMPORTANT: for regular cleaning, do not use alcohols, or acid, solvent or ammonia based-detergents.

INTENDED USE

LINFO-OPAX is a special protective treatment that nourishes and ensures excellent resistance to wear and extreme practicality in routine maintenance.

When applied to wooden floors, LINFO-OPAX completes the protective treatment and gives a matt finish. It is easy to apply and is fast-drying.

INSTRUCTIONS

Shake well before use. Always use at temperatures above +10°C.

After at least 3 days from the Corolle priming treatment (at an average temperature of at least 22°C), when the floor is clean and dry, apply a thin layer of LINFO-OPAX with a cotton cloth. Wait for at least 1 hour and apply another coat, in the same manner. After 2-3 hours the floor can be walked on. In case of high temperatures or for large surfaces, we recommend applying the product very carefully, applying it approximately one metre at a time, in the direction of the wood grain, going from one side of the room to the other, in order not to overlap.

IMPORTANT: The hardening times for natural oil must be assessed according to the temperature, humidity and ventilation, therefore before applying LINFO-OPAX over the entire surface, always always do some test applications since the procedure may compromise the final result. Don't exceed the amount of the product, it can create the whitening of the surface. The protection given by the oil base coat is crucial to ensure stain protection properties.

PROS

- Healthier living environments.
- Increases hydro-oil repellent properties.
- Gives a natural finish without altering the base tone.
- High wear resistance.
- Pleasantly scented.
- Lets the wood breathe.
- It does not release harmful substances during application or after.
- Easy application.

Always run some test applications before applying it to the definitive surfaces.

PROPERTIES

DILUTION: Ready for use.

DRYING/WALKABLE: after 2 hours.

TIME OF REACTION: 48 hours.

YIELD: Approximately 20/35 sqm/l per coat.

HOW TO CLEAN EQUIPMENT: Wash with water.

STORAGE: Closed in the original packaging, in a cool place, away from frost and UV rays, it retains its properties for at least one year.

PACKAGING:
12 1-litre bottles
4 5-litre buckets
2 10-litre buckets

CHARACTERISTICS

APPEARANCE: liquid

COLOUR: milky

ODOUR: pleasantly scented

ACTIVE INGREDIENTS: 19.7%

SOLUBILITY IN WATER: total.

SPECIFIC WEIGHT (20° C): 1.012 kg/l.

PH (20°C): 8.1

HEALTH

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP).

Hazard statements:

EUH210 Safety data sheet available on request.

No danger symbol is required on the label. It must nevertheless be kept out of the reach of children and must not be disposed of in drain water, in order to protect the environment. We nevertheless advise you to adopt good work practices.

LIMITED WARRANTY - READ CAREFULLY

The information provided herein is provided in good faith and on the basis of careful research carried out by New Chemical Prevention. Nevertheless, since conditions and methods of use cannot be controlled by the company, this information does not replace preliminary tests, which are essential in guaranteeing full compliance and safety of the products to the specific application. Therefore New Chemical Prevention guarantees compliance only of the product with current sale specifications. Any compensation to the user or New Chemical Prevention liability are limited exclusively to reimbursing the purchase price or replacing any product that differs from its guaranteed specifications. New Chemical Prevention does not offer any explicit or implicit guarantee regarding product suitability and specific use for its commercial viability, unless the company provides a specific written guarantee of compliance for a specific use. New Chemical Prevention will not be held liable for accidental or indirect damage.

NEW CHEMICAL PREVENTION

VIA MAESTRI DEL LAVORO, 10
41034 FINALE EMILIA
(MODENA) ITALY
TEL+39 0535 91336
FAX+39 0535 93763
INFO@NEWCHEMICAL.IT
WWW.NEWCHEMICAL.IT



NewChemical
PREVENTION