

Printing date 18.02.2008 Revision: 18.02.2008

### 1 Identification of the substance/preparation and of the company/undertaking

Product details

Trade name: 3032 Osmo Polyx-Oil, clear satin

Application of the substance / the

*preparation* Paint

Coating compound/ Surface coating/ paint

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information obtainable

*from:* Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

Information in case of

*emergency:* emergency phone no. Berlin (24h): +49 (0) 30 / 19240

### 2 Hazards identification

*Hazard description:* Not applicable.

Information concerning

particular hazards for human and

environment: The product does not have to be labelled due to the calculation procedure of the

"General Classification guideline for preparations of the EU" in the latest valid version.

Classification system: The classification is according to the latest editions of the EU-lists, and extended by

company and literature data.

## 3 Composition/information on ingredients

Chemical characterization

**Description:** Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 64742-48-9 Naphtha (petroleum), hydrotreated heavy Xn; R 65-66 25-50%

EINECS: 265-150-3

**Additional information:** For the wording of the listed risk phrases refer to section 16.

### 4 First aid measures

General information: Take affected persons out into the fresh air.

Immediately remove any clothing soiled by the product.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult

doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 2)



Printing date 18.02.2008 Revision: 18.02.2008

Trade name: 3032 Osmo Polyx-Oil, clear satin

(Contd. of page 1)

**After skin contact:** Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

Information for doctor:

The following symptoms may

occur: Dizziness
Headache

5 Fire-fighting measures

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant

foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

Special hazards caused by the substance, its products of

combustion or resulting gases: Formation of toxic gases is possible during heating or in case of fire.

Protective equipment:

Mouth respiratory protective device.

Additional information Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

6 Accidental release measures

Person-related safety precautions: Ensure adequate ventilation

Keep away from ignition sources.

Measures for environmental

protection: Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

Measures for cleaning/collecting: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders,

sawdust).

7 Handling and storage

Handling:

*Information for safe handling:* Keep away from heat and direct sunlight.

Use only in well ventilated areas. Keep receptacles tightly sealed. Prevent formation of aerosols.

(Contd. on page 3)



Printing date 18.02.2008 Revision: 18.02.2008

Trade name: 3032 Osmo Polyx-Oil, clear satin

(Contd. of page 2)

Information about fire - and

*explosion protection:* Keep ignition sources away - Do not smoke.

Storage:

Requirements to be met by

storerooms and receptacles: Store only in the original receptacle.

Store in a cool location.

Information about storage in one

common storage facility: Do not store together with alkalis (caustic solutions).

Do not store together with oxidizing and acidic materials.

Further information about

storage conditions: Store in cool, dry conditions in well sealed receptacles.

Keep container tightly sealed.

#### 8 Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

64742-48-9 Naphtha (petroleum), hydrotreated heavy

TWA (8H) Short-term value: 1000 mg/m<sup>3</sup>

Source UK SIA

**Additional information:** The lists valid during the making were used as basis.

Personal protective equipment: General protective and hygienic

measures: Immediately remove all soiled and contaminated clothing

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

**Respiratory protection:** Not necessary if room is well-ventilated.

Use suitable respiratory protective device only when aerosol or mist is formed.

**Protection of hands:** Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/

the preparation.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

To avoid skin problems reduce the wearing of gloves to the required minimum.

Material of gloves Nitrile rubber, NBR

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

(Contd. on page 4)



Printing date 18.02.2008 Revision: 18.02.2008

## Trade name: 3032 Osmo Polyx-Oil, clear satin

(Contd. of page 3)

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

For the permanent contact of a maximum of 15 minutes gloves made of the following materials

are suitable: Nitrile rubber, NBR

Eye protection: Goggles recommended during refilling

**Body protection:** Protective work clothing

## 9 Physical and chemical properties

General Information	
Form:	Viscous
Colour:	Yellowish
Odour:	Mild
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	180°C
Flash point:	>57°C
Ignition temperature:	240°C
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product does not present an explosion hazard.
Explosion limits:	
Lower:	0.6 Vol %
Upper:	7.0 Vol %
Density at 20°C:	0.9 g/cm <sup>3</sup>
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Viscosity:	
Dynamic at 20°C:	140 mPas
Solvent content:	
VOC (EC)	< 500  g/l (VOC-max. = 500  g/l (2010 A/i))

## 10 Stability and reactivity

Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 5)



Printing date 18.02.2008 Revision: 18.02.2008

Trade name: 3032 Osmo Polyx-Oil, clear satin

(Contd. of page 4)

Dangerous reactions Reacts with fabric soaked in the product (e.g. cleaning wool).

Exothermic reaction.

Forms heat. Self igniting.

Dangerous decomposition

products:

Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information:

Warning:

Wash out any used cloth impregnated with this product immedeately after use or store

in an airtight container (danger of self-ingnition).

### 11 Toxicological information

Acute toxicity:

LD/LC50 values relevant for classification:		
64742-48-9 Naphtha (petroleum), hydrotreated heavy		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	>2000 mg/kg (rat)
Inhalative	LC50/4 h	>5 mg/l (rat)
96-29-7 2-butanone oxime		
Oral	LD50	3700 mg/kg (rat)
Dermal	LD50	200-2000 mg/kg (rat)
Inhalative	LC50/4 h	20 mg/l (rat)

Primary irritant effect:

on the skin: At long or repeated contact with skin it may cause dermatitis due to the degreesing

effect of the solvent.

*on the eye:* Irritating effect.

Sensitization: Sensitizing effect by skin contact is possible by prolonged exposure.

Additional toxicological

information: The product is not subject to classification according to the calculation method of the

General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any

harmful effects to our experience and the information provided to us.

## 12 Ecological information

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for

water

(Contd. on page 6)



Printing date 18.02.2008 Revision: 18.02.2008

Trade name: 3032 Osmo Polyx-Oil, clear satin

(Contd. of page 5)

Do not allow product to reach ground water, water course or sewage system.

## 13 Disposal considerations

**Product:** 

**Recommendation** Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

European waste catalogue

08 01 11 waste paint and varnish containing organic solvents or other dangerous substances

15 01 10 packaging containing residues of or contaminated by dangerous substances

Uncleaned packaging:

**Recommendation:** Disposal must be made according to official regulations.

Recommended cleansing agents: Solvent naphtha

### 14 Transport information

Land transport ADR/RID (cross-border)

ADR/RID class: 3 Flammable liquids.

Danger code (Kemler):30UN-Number:1263Packaging group:IIIHazard label:3

Maritime transport IMDG:

IMDG Class:3UN Number:1263Label3Packaging group:IIIEMS Number:F-E,S-EMarine pollutant:NoProper shipping name:PAINT

Air transport ICAO-TI and IATA-DGR:

ICAO/IATA Class: 3
UN/ID Number: 1263
Label 3
Packaging group: III
Proper shipping name: PAINT

(Contd. on page 7)



Printing date 18.02.2008 Revision: 18.02.2008

Trade name: 3032 Osmo Polyx-Oil, clear satin

(Contd. of page 6)

### 15 Regulatory information

Labelling according to EU

guidelines:

The product is not subject to identification regulations under EU Directives and the

Ordinance on Hazardous Materials (German GefStoffV).

Although this product is not subject to identification regulations, we recommend that

the safety suggestions are observed.

Safety phrases: 2 Keep out of the reach of children.

24/25 Avoid contact with skin and eyes.

26 In case of contact with eyes, rinse immediately with plenty of water and seek

medical advice.

46 If swallowed, seek medical advice immediately and show this container or label.

51 Use only in well-ventilated areas.

Special labelling of certain

preparations:

Warning:

Wash out any used cloth impregnated with this product immedeately after use or store

in an airtight container (danger of self-ingnition).

Contains 2-butanone oxime. May produce an allergic reaction. Safety data sheet available for professional user on request.

National regulations:

VOC (EC) < 500 g/l (VOC-max. = 500 g/l (2010 A/i))

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

*Relevant R-phrases* 65 Harmful: may cause lung damage if swallowed.

66 Repeated exposure may cause skin dryness or cracking.

**Department issuing MSDS:** product safety department

Contact: Hr. Dr. Starp

GB