

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 650-007090 HARDWAXOIL MAGIC SATIN  
Print date: 04.09.2014 Revision date: 28.11.2013  
Version: 3.0 Issue date: 28.11.2013

EN  
Page 1 / 9

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifiers**

Article No. (manufacturer/supplier) 650-007090  
Identification of the substance or mixture HARDWAXOIL MAGIC SATIN  
CIRANOVA

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**1.3. Details of the supplier of the safety data sheet**

**supplier (manufacturer/importer/downstream user/distributor)**

Debal Coatings NV  
Industrieweg 29 Telephone: +32 51 30 11 40  
B-8800Beveren-Roeselare Telefax: +32 51 26 48

**Dept. responsible for information:**

Labo:  
E-mail (competent person) info@debalcoatings.be

**1.4. Emergency telephone number**

Emergency telephone number +32 51 30 11 40  
(opening hours Monday to Friday from 8:00 am to 4:30 pm)

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification according to Directive 67/548/EEC or 1999/45/EC**

This mixture is classified as hazardous according to 1999/45/EC.

R10  
R66

Flammable  
Repeated exposure may cause skin dryness or cracking.  
Vapours may cause drowsiness and dizziness.

R67

**2.2. Label elements**

**Labelling (67/548/EEC or 1999/45/EC)**

**Hazard statements**

10 Flammable  
66 Repeated exposure may cause skin dryness or cracking.  
67 Vapours may cause drowsiness and dizziness.

**Precautionary statements**

24 Avoid contact with skin.  
38 In case of insufficient ventilation, wear suitable respiratory equipment.  
51 Use only in well-ventilated areas.  
23 Do not breathe vapour.

**contains:**

n.a.

**Special provisions concerning the labelling of certain mixtures**

99 Contains 2-butanone oxime; phthalic anhydride; Fatty acids C6-19 branched cobalt(2) salts. May produce an allergic reaction.

**2.3. Other hazards**

**SECTION 3: Composition / information on ingredients**

**3.2. Mixtures**

**Product description / chemical characterization**

**Description**

**Hazardous ingredients**

**Classification according to Regulation (EC) No. 1272/2008 [CLP]**

EC No.	REACH No.	Wt %
CAS No.	Chemical name	Remark
INDEX No.	classification	

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) No 453/2010**



Article No.: 650-007090 HARDWAXOIL MAGIC SATIN  
 Print date: 04.09.2014 Revision date: 28.11.2013  
 Version: 3.0 Issue date: 28.11.2013

EN  
 Page 2 / 9

919-857-5	01-2119463258-33 hydrocarbon c9-11 alkanes iso alkanes cyclic <2% aromatics Flam. Liq. 3 H226 / Asp. Tox. 1 H304 / STOT SE 3 H336	25 - 50
918-167-1	01-2119472146-39 Hydrocarbons C11-C12,isoalkanes, < 2% aromatics Flam. Liq. 3 H226 / Asp. Tox. 1 H304	5 - 10
920-901-0	01-2119456810-40-0000 Hydrocarbons C11-C13,isoalkanes, < 2% aromatics Asp. Tox. 1 H304	5 - 10
252-104-2 34590-94-8	01-2119450011-60-0002 (2-methoxymethylethoxy)propanol	2,5 - 5 *
202-496-6 96-29-7 616-014-00-0	01-2119539477-28 2-butanone oxime Carc. 2 H351 / Acute Tox. 4 H312 / Eye Dam. 1 H318 / Skin Sens. 1 H317	0,5 - 1
201-607-5 85-44-9 607-009-00-4	01-2119457017-41 phthalic anhydride Flam. Liq. 3 H226 / Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Dam. 1 H318 / Skin Sens. 1 H317 / Resp. Sens. 1 H334 / STOT SE 3 H335	< 0,5
271-378-4 68551-44-0	Fatty acids, C6-19-branched, zinc salts Aquatic Chronic 2 H411	< 0,5
918-668-5	01-2119455851-35 Hydrocarbons, C9, aromatics Flam. Liq. 3 H226 / STOT SE 3 H335 / Aquatic Chronic 2 H411 / Asp. Tox. 1 H304 / STOT SE 3 H336	< 0,5
270-066-5 68409-81-4	Fatty acids C6-19 branched cobalt(2) salts Acute Tox. 4 H302 / Skin Irrit. 2 H315 / Eye Irrit. 2 H319 / Skin Sens. 1 H317 / Repr. 2 H361 / Aquatic Chronic 2 H411	< 0,5
	Polyaminamidsalz Skin Irrit. 2 H315 / Aquatic Chronic 2 H411	< 0,5
265-185-4 64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy,Low boiling point hydrogen treated naphtha Flam. Liq. 3 H226 / Aquatic Chronic 2 H411 / Asp. Tox. 1 H304 / STOT SE 3 H336	< 0,5

**Classification according to Directive 67/548/EEC or 1999/45/EC**

EC No. CAS No. INDEX No.	REACH No. Chemical name classification	Wt % Remark
919-857-5	01-2119463258-33 hydrocarbon c9-11 alkanes iso alkanes cyclic <2% aromatics R10 / Xn; R65 / R66 / R67	25 - 50
918-167-1	01-2119472146-39 Hydrocarbons C11-C12,isoalkanes, < 2% aromatics Xn; R65 / R66	5 - 10
920-901-0	01-2119456810-40-0000 Hydrocarbons C11-C13,isoalkanes, < 2% aromatics Xn; R65 / R66	5 - 10
252-104-2 34590-94-8	01-2119450011-60-0002 (2-methoxymethylethoxy)propanol	2,5 - 5 *
202-496-6 96-29-7 616-014-00-0	01-2119539477-28 2-butanone oxime Carc.Cat.3; R40 / Xn; R21 / Xi; R41 / R43	0,5 - 1

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 650-007090 HARDWAXOIL MAGIC SATIN  
Print date: 04.09.2014 Revision date: 28.11.2013  
Version: 3.0 Issue date: 28.11.2013

EN  
Page 3 / 9

201-607-5 85-44-9 607-009-00-4 271-378-4 68551-44-0	01-2119457017-41 phthalic anhydride Xn; R22 / Xi; R37/38-41 / R42/43	< 0,5
918-668-5	Fatty acids, C6-19-branched zinc salts N; R51-53	< 0,5
270-066-5 68409-81-4	01-2119455851-35 Hydrocarbons, C9, aromatics R10 / Xi; R37 / N; R51-53 / Xn; R65 / R66 / R67	< 0,5
265-185-4 64742-82-1	Fatty acids C6-19 branched cobalt(2) salts Xn; R22 / Xi; R38 / R43 / N; R51-53 / Repr.Cat.3; R62	< 0,5
	Polyaminamidsalz Xi; R38 / N; R51-53	< 0,5
	Naphtha (petroleum), hydrodesulfurized heavy R10 / N; R51-53 / Xn; R65 / R66 / R67	< 0,5

**Additional information**

\* Substance with a common (EC) occupational exposure limit value.

Full text of R-phrases: see section 16.

Full text of H-phrases: see section 16.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

**General information**

In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness give nothing by mouth, place in recovery position and seek medical advice.

**In case of inhalation**

Remove casualty to fresh air and keep warm and at rest. In case of irregular breathing or respiratory arrest provide artificial respiration.

**Following skin contact**

Remove contaminated, saturated clothing immediately. After contact with skin, wash immediately with plenty of water and soap. Do not use solvents or thinners.

**After eye contact**

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Seek medical advice immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Seek medical advice immediately. Keep victim calm. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

In all cases of doubt, or when symptoms persist, seek medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

**Suitable extinguishing media**

alcohol resistant foam, carbon dioxide, Powder, spray mist, (water)

**Extinguishing media which must not be used for safety reasons:**

strong water jet

**5.2. Special hazards arising from the substance or mixture**

Dense black smoke occurs during fire. Inhaling hazardous decomposing products can cause serious health damage.

**5.3. Advice for firefighters**

Provide a conveniently located respiratory protective device. Cool closed containers that are near the source of the fire. Do not allow water used to extinguish fire to enter drains, ground or waterways. Treat runoff as hazardous.

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) No 453/2010**

Article No.: 650-007090 HARDWAXOIL MAGIC SATIN  
Print date: 04.09.2014 Revision date: 28.11.2013  
Version: 3.0 Issue date: 28.11.2013

EN  
Page 4 / 9



## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Keep away from sources of ignition. Ventilate affected area. Do not breathe vapours.

### 6.2. Environmental precautions

Do not allow to enter into surface water or drains. If the product contaminates lakes, rivers or sewages, inform competent authorities in accordance with local regulations.

### 6.3. Methods and material for containment and cleaning up

Isolate leaked material using non-flammable absorption agent (e.g. sand, earth, vermiculit, diatomaceous earth) and collect it for disposal in appropriate containers in accordance with the local regulations (see chapter 13). Clean using cleansing agents. Do not use solvents.

### 6.4. Reference to other sections

Observe protective provisions (see chapter 7 and 8).

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

#### Advices on safe handling

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Electrical equipment must be protected meeting the accepted standard. Product may become electrostatically charged. Provide earthing of containers, equipment, pumps and ventilation facilities. Anti-static clothing including shoes are recommended. Floors must be electrically conductive. Keep away from heat sources, sparks and open flames. Use only spark proof tools. Avoid contact with skin, eyes and clothes. Do not inhale dusts, particulates and spray mist when using this preparation. Avoid respiration of swarf. When using do not eat, drink or smoke. Personal protection equipment: refer to chapter 8. Do not empty containers with pressure - no pressure vessel! Always keep in containers that correspond to the material of the original container. Follow the legal protection and safety regulations.

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later.

To avoid the risks of fires, all contaminated materials should be stored in purpose-built containers or in metal containers with tight-fitting self-closing lids.

laid out flat in a single layer to dry

placed in a closed metal container soaked with water

washed out well with warm soapy water before disposal

Contaminated materials should be removed from the workplace at the end of each working day and be stored outside.

#### Precautions against fire and explosion:

Vapours are heavier than air. Vapours form explosive mixtures with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Storage in accordance with the Ordinance on Industrial Safety and Health (BetrSiVO). Keep container tightly closed. Do not empty containers with pressure - no pressure vessel! Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks. Soils have to conform to the "Guidelines for avoidance of ignition hazards due to electrostatic charges (BGR 132)".

#### Hints on joint storage

Keep away from strongly acidic and alkaline materials as well as oxidizers.

#### Further information on storage conditions

Take care of instructions on label. Store in a well-ventilated and dry room at temperatures between 15 °C and 25 °C. Protect from heat and direct sunlight. Keep container tightly closed. Remove all sources of ignition. Smoking is forbidden. Access only for authorised persons. Store carefully closed containers upright to prevent any leaks.

### 7.3. Specific end use(s)

Observe technical data sheet. Observe instructions for use.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limit values:

silica amorf

EC No. 231-545-4 / CAS No. 7631-86-9

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 650-007090 HARDWAXOIL MAGIC SATIN  
Print date: 04.09.2014 Revision date: 28.11.2013  
Version: 3.0 Issue date: 28.11.2013

EN  
Page 5 / 9

WEL, TWA: 2,4 mg/m<sup>3</sup>  
Remark: (Silica, amorphous; respirable fraction)  
WEL, TWA: 6 mg/m<sup>3</sup>  
Remark: (Silica, amorphous; inhalable fraction)  
(2-methoxymethylethoxy)propanol  
EC No. 252-104-2 / CAS No. 34590-94-8  
WEL, TWA: 308 mg/m<sup>3</sup>; 50 ppm

**Additional information**

TWA : long-term occupational exposure limit value  
STEL : short-term occupational exposure limit value  
Ceiling : peak limitation

**8.2. Exposure controls**

Provide good ventilation. This can be achieved with local or room suction. If this should not be sufficient to keep aerosol and solvent vapour concentration below the exposure limit values, a suitable respiratory protection must be used.

**Occupational exposure controls**

**Respiratory protection**

If concentration of solvents is beyond the occupational exposure limit values, approved and suitable respiratory protection must be used. Observe the wear time limits according GefStoffV in combination with the rules for using respiratory protection apparatus (BGR 190). Use only respiratory protection equipment with CE-symbol including four digit test number.

**Hand protection**

For prolonged or repeated handling the following glove material must be used: NBR (Nitrile rubber)  
Thickness of the glove material > 0,4 mm ; Breakthrough time (maximum wearing time) > 480 min.  
Observe the instructions and details for use, storage, maintenance and replacement provided by the protective glove manufacturer. Penetration time of glove material depending on intensity and duration of exposure to skin. Recommended glove articles DIN EN 374  
Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

**Eye protection**

Wear closely fitting protective glasses in case of splashes.

**Protective clothing**

Wear antistatic clothing of natural fibers (cotton) or heat resistant synthetic fibers.

**Protective measures**

After contact clean skin thoroughly with water and soap or use appropriate cleanser.

**Environmental exposure controls**

Do not allow to enter into surface water or drains. See chapter 7. No additional measures necessary.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

**Appearance:**

Physical state liquid  
Colour refer to label  
Odour characteristic

Safety relevant basis data	Unit	Method	Remark
Flash point:	< 55 °C		
Ignition temperature in °C:	n.b.		
Lower explosion limit:	n.b.		
Upper explosion limit:	n.b.		
Vapour pressure at 20 °C:	n.b.		
Density at 20 °C:	0,90 g/cm <sup>3</sup>		
Water solubility (g/L):	insoluble		
pH at 20 °C:	-		
Viscosity at 20 °C:	50 s 4 mm	DIN 53211	
Solvent separation test (%):	< 3 %	ADR/RID	
Solid content (%):	45,55 Wt %		
solvent content:			
Organic solvents:	53,2 Wt %		
Water:	0,3 Wt %		

**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010

Article No.: 650-007090 HARDWAXOIL MAGIC SATIN  
Print date: 04.09.2014 Revision date: 28.11.2013  
Version: 3.0 Issue date: 28.11.2013

EN  
Page 6 / 9



9.2. **Other information**

**SECTION 10: Stability and reactivity**

10.1. **Reactivity**

10.2. **Chemical stability**

Stable when applying the recommended regulations for storage and handling. Further information on correct storage: refer to chapter 7.

10.3. **Possibility of hazardous reactions**

Keep away from strong acids, strong bases and strong oxidizing agents to avoid exothermic reactions.

10.4. **Conditions to avoid**

Hazardous decomposition byproducts may form with exposure to high temperatures.

10.5. **Incompatible materials**

10.6. **Hazardous decomposition products**

Hazardous decomposition byproducts may form with exposure to high temperatures, e.g.: carbon dioxide, carbon monoxide, smoke, nitrogen oxides.

**SECTION 11: Toxicological information**

No data on preparation itself available.

11.1. **Information on toxicological effects**

**Acute toxicity**

Toxicological data are not available.

**Irritant and corrosive effects**

Toxicological data are not available.

**Sensitisation**

Toxicological data are not available.

**Specific target organ toxicity**

Toxicological data are not available.

**Aspiration hazard**

Toxicological data are not available.

**Practical experience/human evidence**

Other observations:

Inhaling of solvent components above the MWC-value can lead to health damage, e.g. irritation of the mucous membrane and respiratory organs, as well as damage to the liver, kidneys and the central nerve system. Indications for this are: headache, dizziness, fatigue, amyosthenia, drowsiness, in serious cases: unconsciousness. Solvents may cause some of the aforementioned effects through skin resorption. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non-allergic contact dermatitis and/or absorption through skin. Splashing may cause eye irritation and reversible damage.

**Overall Assessment on CMR properties**

The ingredients in this preparation do not meet the criteria for classification as CMR category 1 or 2 according to 67/548/EEC.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified according to the toxicological dangers. See chapters 2 and 15 for details.

**SECTION 12: Ecological information**

**overall evaluation**

There is no information available on the preparation itself .

Do not allow to enter into surface water or drains.

12.1. **Toxicity**

Toxicological data are not available.

12.2. **Persistence and degradability**

Toxicological data are not available.

12.3. **Bioaccumulative potential**

Toxicological data are not available.

12.4. **Mobility in soil**



**Safety Data Sheet**  
according to Regulation (EC) No. 1907/2006 (REACH)  
according to Regulation (EU) No 453/2010



Article No.: 650-007090 HARDWAXOIL MAGIC SATIN  
Print date: 04.09.2014 Revision date: 28.11.2013  
Version: 3.0 Issue date: 28.11.2013

EN  
Page 7 / 9

Toxicological data are not available.

**12.5. Results of PBT assessment**

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

**12.6. Other adverse effects**

**SECTION 13: Disposal considerations**

**13.1. Waste treatment methods**

**Appropriate disposal / Product Recommendation**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.

**List of proposed waste codes/waste designations in accordance with EWC**

080111 waste paint and varnish containing organic solvents or  
other dangerous substances

**packaging**

**Recommendation**

Non-contaminated packages may be recycled. Vessels not properly emptied are special waste.

**SECTION 14: Transport information**

**14.1. UN number**

1263

**14.2. UN proper shipping name**

Land transport (ADR/RID): Verferwante produkten  
Sea transport (IMDG): PAINT  
Air transport (ICAO-TI / IATA-DGR): Paint

**14.3. Transport hazard class(es)**

3

**14.4. Packing group**

III

**14.5. Environmental hazards**

Land transport (ADR/RID) n.a.  
Marine pollutant n.a.

**14.6. Special precautions for user**

Transport always in closed, upright and safe containers. Make sure that persons transporting the product know what to do in case of an accident or leakage.

Advices on safe handling: see parts 6 - 8

**Additional information**

**Land transport (ADR/RID)**

tunnel restriction code D/E

**Sea transport (IMDG)**

EmS-No. F-E, S-E

**14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

not applicable

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU legislation**

**Information according to 1999/13/EC about limitation of emissions of volatile organic compounds (VOC-guideline).**

VOC-value (in g/L) ISO 11890-2: 489,273

VOC-value (in g/L) ASTM D 2369: 490,622

**according to EU-regulation 2004/42/EC (appendix II)**

**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) No 453/2010**



Article No.: 650-007090 HARDWAXOIL MAGIC SATIN  
 Print date: 04.09.2014 Revision date: 28.11.2013  
 Version: 3.0 Issue date: 28.11.2013

EN  
 Page 8 / 9

EU limit value for this product (cat. (Cat. A/i)): 600 g/l (2007)/500 g/l (2010).  
 This product contains max 489,273 g/l VOC.

**National regulations**

**Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.  
 Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

**Other regulations, restrictions and prohibition regulations**

**15.2. Chemical Safety Assessment**

**For the following substances of this preparation a chemical safety assessment has been carried out:**

EC No. CAS No.	Chemical name	REACH No.
202-496-6 96-29-7	2-butanone oxime	01-2119539477-28
201-607-5 85-44-9	phthalic anhydride	01-2119457017-41
919-857-5	hydrocarbon c9-11 alkanes iso alkanes cyclic <2% aromatics	01-2119463258-33
252-104-2 34590-94-8	(2-methoxymethylethoxy)propanol	01-2119450011-60-0002
918-668-5	Hydrocarbons, C9, aromatics	01-2119455851-35
918-167-1	Hydrocarbons C11-C12,isoalkanes, < 2% aromatics	01-2119472146-39
920-901-0	Hydrocarbons C11-C13,isoalkanes, < 2% aromatics	01-2119456810-40-0000

**SECTION 16: Other information**

**Relevant R-and H-phrases (Number and full text):**

Flam. Liq. 3 / H226	flammable liquids	Flammable liquid and vapour.
Asp. Tox. 1 / H304	Aspiration hazard	May be fatal if swallowed and enters airways.
STOT SE 3 / H336	Specific target organ toxicity (single exposure)	May cause drowsiness or dizziness.
Carc. 2 / H351	Carcinogenicity	Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard). Harmful in contact with skin.
Acute Tox. 4 / H312	Acute toxicity (dermal)	Causes serious eye damage.
Eye Dam. 1 / H318	Serious eye damage/eye irritation	May cause an allergic skin reaction.
Skin Sens. 1 / H317	respiratory or skin sensitisation	Harmful if swallowed.
Acute Tox. 4 / H302	Acute toxicity (oral)	Causes skin irritation.
Skin Irrit. 2 / H315	skin corrosion/irritation	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Resp. Sens. 1 / H334	respiratory or skin sensitisation	May cause respiratory irritation.
STOT SE 3 / H335	Specific target organ toxicity (single exposure)	
Aquatic Chronic 2 / H411	Hazardous to the aquatic environment	Toxic to aquatic life with long lasting effects.
Eye Irrit. 2 / H319	Serious eye damage/eye irritation	Causes serious eye irritation.
Repr. 2 / H361	Reproductive toxicity	Suspected of damaging fertility or the unborn child (state specific effect if known) (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).
Carc.Cat.3; R40	Carcinogenic Cat. 3 (Carc. Cat. 3)	Limited evidence of a carcinogenic effect.
Xn; R21	Harmful	Harmful in contact with skin.
Xi; R41	Irritant	Risk of serious damage to eyes.
R43		May cause sensitization by skin contact.
Xn; R22	Harmful	Harmful if swallowed.
Xi; R37/38-41	Irritant	Irritating to respiratory system and skin. Risk of serious damage to eyes.
R42/43		May cause sensitization by inhalation and skin contact.
Xi; R38	Irritant	Irritating to skin.
N; R51-53	Dangerous for the environment	Toxic to aquatic life. May cause long-term adverse effects in the aquatic environment.
Repr.Cat.3; R62	Reproductive toxic Cat.3 (Repr. Cat. 3)	Possible risk of impaired fertility.
R10		Flammable



**Safety Data Sheet**  
**according to Regulation (EC) No. 1907/2006 (REACH)**  
**according to Regulation (EU) No 453/2010**



Article No.: 650-007090 HARDWAXOIL MAGIC SATIN  
Print date: 04.09.2014 Revision date: 28.11.2013  
Version: 3.0 Issue date: 28.11.2013

EN  
Page 9 / 9

Xn; R65 R66	Harmful	Harmful: may cause lung damage if swallowed. Repeated exposure may cause skin dryness or cracking.
R67 Xi; R37	Irritant	Vapours may cause drowsiness and dizziness. Irritating to respiratory system.

**Additional information**

The information supplied on this safety data sheet complies with our current level of knowledge as well as with national and EU regulations. Without written approval, the product must not be used for purposes different from those mentioned in chapter 1. It is always the user's duty to take any necessary measures for meeting the requirements laid down by local rules and regulations. The details in this safety data sheet describe the safety requirements of our product and are not to be regarded as guaranteed attributes of the product.