TERRA COLLECTION



COMPOSITION

Microcrystalline waxes, Carnauba wax, beeswax, paraffin waxes, wax and resin emulsions, fluoropolymers, antifouling agent, essences, water.

PROFILE

SINTESI 3/P is a combination of various types of fine wax emulsions with stain protection properties, featuring excellent wettability and high substrate bonding ability. As well as high resistance to wear, **SINTESI 3/P** gives floors a satin-finish result.

IMPORTANT: for regular cleaning, do not use alcohols, or acid, solvent or ammonia based-detergents.

Sintesi 3/P

SPECIAL FINISHING WAX FOR INTERIORS

INTENDED USE

SINTESI 3/P is a water-based finishing wax suitable for a wide variety of materials such as: cotto, terracotta, concrete, marble and unpolished natural stone, to be used after the application of primers, such as: Linfocot, Kripton HS, Olio Dodici, Luxor FB, etc... It can be applied directly to structured surfaces made of porcelain stoneware. Suitable only for indoor surfaces, it ensures high mechanical resistance.

IMPORTANT: before using the product always make sure that the manufacturing companies of the materials do not recommend against using it.

INSTRUCTIONS

Shake well before use. Always use at temperatures above $\pm 10^{\circ}$ C. After the application of a primer, when the surface is dry, apply **SINTESI 3/P**, using a cotton cloth and brush or applicator.

If necessary, apply a second coat using the same method.

It does not require polishing. **SINTESI 3/P** can also be used as a dust repellent on indoor face bricks, or on porcelain stoneware with a structured surface, to facilitate maintenance, without altering the colour.

PROS

- Integrates and completes the treatment.
- Increases stain protector action.
- Gives a very strong pearl effect finish.
- Easy cleaning.
- Simple to use.
- Gives a pleasant waxed effect finish.
- Ensures an even result.
- It does not release harmful substances during application or after.
- Pleasantly scented

PROPERTIES

DILUTION: Ready for use. DRYING: Approximately 1-2 hours (at 20°C) between applications. Maximum hardness after 48 hours. YIELD: Approximately 18-26 sqm/l per coat. HOW TO CLEAN EQUIPMENT: Wash with water. STORAGE: Closed in the original packaging, in a cool place away from frost and UV rays, it retains its properties for at least one year. PACKAGING: 12 1-litre bottles

4 5-litre buckets

2 10-litre buckets

CHEMICAL AND PHYSICAL CHARACTERISTICS

APPEARANCE: liquid COLOUR: milky ODOUR: pleasantly scented ACTIVE INGREDIENTS: 20% PH (20°C): 8.7 SPECIFIC WEIGHT (20°C): 1.018 kg/l. SOLUBILITY IN WATER: total

HEALTH

The product is not classified as hazardous pursuant to the provisions set forth in EC Regulation 1272/2008 (CLP). However, since the product contains hazardous substances in concentrations such as to be declared in section no. 3, it requires a safety data sheet with appropriate information, compliant to EC Regulation 1907/2006 and subsequent amendments. No danger symbol is required on the label It must nevertheless be kept out of the reach of children and must not be disposed of in drain

water, in order to protect the environment. We nevertheless advise you to adopt good work practices.

Always run some test applications before applying it to the definitive surfaces

LIMITED WARRANTY - READ CAREFULLY

The information provided herein is provided in good faith and on the basis of careful research carried out by New Chemical Prevention. Nevertheless, since conditions and methods of use cannot be controlled by the company, this information does not replace preliminary tests, which are essential in guaranteeing full compliance and safety of the products to the specific application. Therefore New Chemical Prevention guarantees compliance only of the product with current sale specifications. Any compensation to the user or New Chemical Prevention liability are limited exclusively to reimbursing the purchase price or replacing any product that differs from its guaranteed specifications. New Chemical Prevention does not offer any explicit or implicit guarantee regarding product suitability and specific use for its commercial viability, unless the company provides a specific written guarantee of compliance for a specific use. New Chemical Prevention will not be held liable for accidental or indirect damage. NEW CHEMICAL PREVENTION VIA MAESTRI DEL LAVORO, 10 41034 FINALE EMILIA (MODENA) ITALY TEL+39 0535 91336 FAX+39 0535 93763 INFO@NEWCHEMICAL.IT WWW.NEWCHEMICAL.IT

