SOLID'OIL PAGE 1/9

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 453/2010)

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name: SOLID'OIL

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Registered company name: BLANCHON.

Address: 28, rue Charles Martin B.P. 105.69190.SAINT FONS.FRANCE.

Telephone: 00.33.4.72.89.06.09. Fax: 00.33.4.72.89.06.02.

fds@blanchon.com

1.4. Emergency telephone number: 00.33.1.45.42.59.59.

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Repeated exposure may cause skin dryness or cracking (EUH066).

May produce an allergic reaction (EUH208).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

May produce an allergic reaction.

Repeated exposure may cause skin dryness or cracking (R 66).

Aquatic environmental hazard, chronic toxicity: harmful (R 52/53).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Additional labeling:

EUH208 Contains 2-OXY-BUTANON. May produce an allergic reaction.

EUH208 Contains COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.
P103 Read label before use.
Precautionary statements - Prevention :
P273 Avoid release to the environment.

Precautionary statements - Disposal:

P501 Dispose of contents / container to an approved landfill.

2.3. Other hazards

The mixture does not contain any substances classified as 'Substances of Very High Concern' (SVHC) by the European CHemical s Agency (ECHA) under article 57 of REACH: http://echa.europa.eu/fr/candidate-list-table

The mixture satisfies neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures

Composition:

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006

SOLID'OIL PAGE 2/9

Identification	(EC) 1272/2008	67/548/EEC	Note	%
CAS: 64742-48-9	GHS08	Xn	Р	25 <= x % < 50
EC: 918-481-9	Dgr	Xn;R65		
REACH: 01-2119457273-39	Asp. Tox. 1, H304	R66		
HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS	EUH:066			
INDEX: 616-014-00-0	GHS08, GHS05, GHS07	Xn	[2]	0 <= x % < 2.5
CAS: 96-29-7	Dgr	Carc. Cat. 3;R40		
EC: 202-496-6	Carc. 2, H351	Xn;R21		
REACH: 01-2119539477-28-0004	Acute Tox. 4, H312	Xi;R41-R43		
2-OXY-BUTANON	Eye Dam. 1, H318			
	Skin Sens. 1, H317			
CAS: 136-52-7	GHS09, GHS07, GHS08	Xn,N	[2]	0 <= x % < 2.5
EC: 205-250-6	Wng	Repr. Cat. 3;R62		
REACH: 01-2119524678-29	Skin Sens. 1, H317	Xi;R43		
COBALT BIS(2-ETHYLHEXANOATE)	Repr. 2, H361f	N;R50/53		
	Aquatic Acute 1, H400			
	M Acute = 1			
	Aquatic Chronic 1, H410			
	M Chronic = 1			
CAS: 22464-99-9	GHS08	Xn	F [2]	0 <= x % < 2.5
EC: 245-018-1	Wng	Repr. Cat. 3;R63		
REACH: 01-2119979088-21	Repr. 2, H361d			
OCTANOIC ACID ZIRCONIUM SALT				
INDEX: 601-043-00-3	GHS02, GHS07, GHS09	Xn,N	[1]	0 <= x % < 2.5
CAS: 95-63-6	Wng	Xn;R20		
EC: 202-436-9	Flam. Liq. 3, H226	Xi;R36/37/38		
1,2,4-TRIMETHYLBENZENE	Acute Tox. 4, H332	N;R51/53		
	Eye Irrit. 2, H319	R10		
	STOT SE 3, H335			
	Skin Irrit. 2, H315			
	Aquatic Chronic 2, H411			
INDEX: 601-025-00-5	GHS02, GHS07, GHS09	Xi,N	[1]	0 <= x % < 2.5
CAS: 108-67-8	Wng	Xi;R37		
EC: 203-604-4	Flam. Liq. 3, H226	N;R51/53		
MESITYLENE	STOT SE 3, H335	R10		
	Aquatic Chronic 2, H411			

Information on ingredients:

- [1] Substance for which maximum workplace exposure limits are available.
- [2] Carcinogenic, mutagenic or reprotoxic (CMR) substance.

Note P: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS 200-753-7).

SECTION 4: FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

4.1. Description of first aid measures

In the event of exposure by inhalation:

In the event of an allergic reaction, seek medical attention.

In the event of splashes or contact with eyes:

Wash thoroughly with soft, clean water for 15 minutes holding the eyelids open.

In the event of splashes or contact with skin:

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

In the event of an allergic reaction, seek medical attention.

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006

SOLID'OIL PAGE 3/9

In the event of swallowing:

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Keep the person exposed at rest. Do not force vomiting.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5: FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

In the event of a fire, use:

- sprayed water or water mist
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO2)

Unsuitable methods of extinction

In the event of a fire, do not use:

- water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed:

- carbon monoxide (CO)
- carbon dioxide (CO2)

5.3. Advice for firefighters

No data available.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

For non first aid worker

Avoid any contact with the skin and eyes.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7: HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

This Safety Data Sheet is prepared in accordance with

Annex II to Regulation (EC) No 1907/2006

SOLID'OIL PAGE 4/9

Ensure that there is adequate ventilation, especially in confined areas.

Fire prevention:

Handle in well-ventilated areas.

Prevent access by unauthorised personnel.

Recommended equipment and procedures:

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Packages which have been opened must be reclosed carefully and stored in an upright position.

Prohibited equipment and procedures:

No smoking, eating or drinking in areas where the mixture is used.

7.2. Conditions for safe storage, including any incompatibilities

No data available.

Storage

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits:

- European Union (2009/161/EU, 2006/15/EC, 2000/39/EC, 98/24/EC)

CAS	VME-mg/m3:	VME-ppm:	VLE-mg/m3:	VLE-ppm:	Notes :
95-63-6	100	20	-	ı	-
108-67-8	100	20	-	ı	-

- France (INRS - ED984 :2008) :

CAS	VME-ppm :	VME-mg/m3:	VLE-ppm:	VLE-mg/m3:	Notes :	TMP No:
95-63-6	20	100	50	250	-	84
108-67-8	20	100	50	250	-	84

- UK / WEL (Workplace exposure limits, EH40/2005, 2007) :

CAS	TWA:	STEL:	Ceiling:	Definition :	Criteria :
95-63-6	25 ppm	-	-	-	-
108-67-8	25 ppm	_	_	_	_

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

OCTANOIC ACID ZIRCONIUM SALT (CAS: 22464-99-9)

Final use: Workers.

Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 6.49 mg/kg body weight/day

Exposure method: Inhalation.

Potential health effects: Long term systemic effects.

DNEL: 32.97 mg of substance/m3

Final use: Consumers.

Exposure method: Ingestion.

Potential health effects: Long term systemic effects.

DNEL: 4.51 mg/kg body weight/day Exposure method: Dermal contact.

Potential health effects: Long term systemic effects.

DNEL: 3.25 mg/kg body weight/day Exposure method: Inhalation.

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006

SOLID'OIL PAGE 5/9

Potential health effects: Long term systemic effects.

DNEL: 8.13 mg of substance/m3

Predicted no effect concentration (PNEC):

OCTANOIC ACID ZIRCONIUM SALT (CAS: 22464-99-9)

Environmental compartment: Soil.

PNEC: 1.06 mg/kg

Environmental compartment: Fresh water.

PNEC: 0.36 mg/l

Environmental compartment: Sea water.

PNEC: 0.036 mg/l

Environmental compartment: Fresh water sediment.

PNEC: 6.37 mg/kg

Environmental compartment: Marine sediment.

PNEC: 0.637 mg/kg

Environmental compartment: Waste water treatment plant.

PNEC: 71.7 mg/l 8.2. Exposure controls

Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE):





Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question: other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended:

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVA (Polyvinyl alcohol)

Recommended properties:

- Impervious gloves in accordance with standard EN374

- Body protection

Avoid skin contact.

Wear suitable protective clothing.

Suitable type of protective clothing:

In the event of substantial spatter, wear liquid-tight protective clothing against chemical risks (type 3) in accordance with EN14605 to prevent skin contact.

In the event of a risk of splashing, wear protective clothing against chemical risks (type 6) in accordance with EN13034 to prevent skin contact.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

General information:

Physical state: Viscous liquid.

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006

SOLID'OIL PAGE 6/9

Important health, safety and environmental information

pH:Not stated.

Neutral

Boiling point/boiling range : 170 °C. Flash Point Interval : 60°C < PE <= 93°C

Vapour pressure (50°C): Below 110 kPa (1.10 bar).

Density: < 1

Water solubility: Insoluble.

Melting point/melting range: -20 °C.

Self-ignition temperature: 200 °C.

Decomposition point/decomposition range: Not relevant.

9.2. Other information V.O.C: 325g/l

SECTION 10: STABILITY AND REACTIVITY

10.1. Reactivity

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

10.4. Conditions to avoid

10.5. Incompatible materials

10.6. Hazardous decomposition products

The thermal decomposition may release/form:

- carbon monoxide (CO)
- carbon dioxide (CO2)

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

11.1.1. Substances

Acute toxicity:

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)

Oral route: LD50 > 5000 mg/kg

OECD Guideline 401 (Acute Oral Toxicity)
Species: Rat (recommended by the CLP)

Dermal route: LD50 > 5000 mg/kg

OECD Guideline 402 (Acute Dermal Toxicity) Species: Rabbit (recommended by the CLP)

Inhalation route: LC50 > 4951 mg/l

OECD Guideline 403 (Acute Inhalation Toxicity) Species: Rat (recommended by the CLP)

11.1.2. Mixture

Respiratory or skin sensitisation:

Contains at least one sensitising substance. May cause an allergic reaction.

SECTION 12: ECOLOGICAL INFORMATION

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006

SOLID'OIL PAGE 7/9

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity

12.1.1. Substances

HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9)

Fish toxicity: LC50 = 1000 mg/l Species: Oncorhynchus mykiss Duration of exposure: 96 h

Crustacean toxicity: EC50 = 1000 mg/l

Species : Daphnia magna
Duration of exposure : 48 h
Algae toxicity : ECr50 = 1000 mg/l

Species: Pseudokirchnerella subcapitata

Duration of exposure: 72 h

12.1.2. Mixtures

No aquatic toxicity data available for the mixture.

12.2. Persistence and degradability

12.2.1. Substances

COBALT BIS(2-ETHYLHEXANOATE) (CAS: 136-52-7)

Biodegradability: no degradability data is available, the substance is considered as not degrading quickly. HYDROCARBONS, C10-C13, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS (CAS: 64742-48-9) Biodegradability: no degradability data is available, the substance is considered as not degrading quickly.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available.

12.6. Other adverse effects

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste:

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging:

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14: TRANSPORT INFORMATION

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2013 - IMDG 2012 - ICAO/IATA 2014).

Exempt from transport classification and labelling.

SECTION 15: REGULATORY INFORMATION

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
- Classification and labelling information included in section 2:

The following regulations have been used:

- Directive 67/548/EEC and its adaptations

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006

SOLID'OIL PAGE 8/9

- Directive 1999/45/EC and its adaptations
- Regulation EC 1272/2008 modified by regulation EC 618/2012
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.

Container information:

No data available.

- Particular provisions :

No data available.

15.2. Chemical safety assessment

No data available.

SECTION 16: OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

In compliance with directives 67/548/EEC, 1999/45/EC and their amendments.

Contains:

Contains 616-014-00-0 2-OXY-BUTANON. May produce an allergic reaction.

Contains EC 205-250-6 COBALT BIS(2-ETHYLHEXANOATE). May produce an allergic reaction.

Risk phrase:

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 66 Repeated exposure may cause skin dryness or cracking.

Safety phrase:

S 2 Keep out of the reach of children.

S 23 Do not breathe vapour.

S 24 Avoid contact with skin.

S 62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

Title for H, EUH and R indications mentioned in section 3:

H226	Flammable liquid and vapour.
LISOA	May be fetal if awallowed and

May be fatal if swallowed and enters airways. H304

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H361d Suspected of damaging the unborn child.

H361f Suspected of damaging fertility.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

R 10 Flammable.

R 20 Harmful by inhalation. R 21 Harmful in contact with skin.

R 36/37/38 Irritating to eyes, respiratory system and skin.

R 37 Irritating to respiratory system.

R 40.C3 Limited evidence of a carcinogenic effect.

R 41 Risk of serious damage to eyes.

R 43 May cause sensitisation by skin contact.

R 50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006

SOLID'OIL PAGE 9/9

R 62.F3 Possible risk of impaired fertility.

R 63.G3 Possible risk of harm to the unborn child.R 65 Harmful: may cause lung damage if swallowed.

R 66 Repeated exposure may cause skin dryness or cracking.

Abbreviations:

DNEL: Derived No-Effect Level

PNEC : Predicted No-Effect Concentration CMR: Carcinogenic, mutagenic or reprotoxic.

ADR: European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods. IATA : International Air Transport Association. ICAO : International Civil Aviation Organisation

RID: Regulations concerning the International carriage of Dangerous goods by rail.

This Safety Data Sheet is prepared in accordance with Annex II to Regulation (EC) No 1907/2006